

CABINETS FOR CONTROLLERS SERIE 5

Ref: 5C16

- * **16 modules** maximum
- * **Supply** 230V/400V (50Hz/60Hz) 3ph + N
- * **Venting with filtered air**
- * **Protection** by circuit breaker
- * Electronic **protection** against neutral malfunction
- * **Communication** upper and lower alarm and 2nd setpoint according to the **EUROMAP 17**.



W534 x H436 x D470

Ref: 5C12

- * **12 modules** maximum
- * **Supply** 230V/400V (50Hz/60Hz) 3ph + N
- * **Venting with filtered air**
- * **Protection** by circuit breaker
- * Electronic **protection** against neutral malfunction
- * **Communication** upper and lower alarm and 2nd setpoint according to the **EUROMAP 17**.



W735 x H216 x D470

Ref: 5C8

- * **8 modules** maximum
- * **Supply** 230V/400V (50Hz/60Hz) 3ph + N
- * **Venting with filtered air**
- * **Protection** by circuit breaker
- * Electronic **protection** against neutral malfunction
- * **Communication** upper and lower alarm and 2nd setpoint according to the **EUROMAP 17**.



W534 x H216 x D470

Ref: 5C4

- * **4 modules** maximum
- * **Supply** 230V/400V 3ph or 400V 3ph + N (50Hz/60Hz)
- * **Ventilated**
- * **Protection** by circuit breaker
- * **Communication** upper and lower alarm and 2nd setpoint according to the **EUROMAP 17**.



W328 x H216 x D430

TEMPERATURE CONTROLLER FOR HOT RUNNER MOULDING SYSTEMS

Ref: **5C16**

Power input cable 5x6 mm²
4,3 meters long
Cable allows maximum working power:
16 kW 3ph 230V - 24 kW 3ph 400V
Dimensions : W534 x H436 x D470



TYPES de cordons compatibles
3CP4 et 3CJ4 ou 3CP6 et 3CJ6

Ref: **5C12**

Power input cable 5x6 mm²
4,3 meters long
Cable allows maximum working power:
16 kW 3ph 230V - 24 kW 3ph 400V
Dimensions : W735 x H216 x D470



TYPES of output leads
3CP4 and 3CJ4 or 3CP6 and 3CJ6

Ref: **5C8**

Power input cable 5x6 mm²
4,3 meters long
Cable allows maximum working power:
16 kW 3ph 230V - 24 kW 3ph 400V
Dimensions : W534 x H216 x D470



TYPES of output leads
3CP4 and 3CJ4 or 3CP6 and 3CJ6

Ref: **5C4**

Power input cable 5x4 mm²
4,3 meters long
Cable allows maximum working power:
12 kW 3ph 230V - 20 kW 3ph 400V
Dimensions : W328 x H216 x D430



TYPES of output leads
3CP4 and 3CJ4